


JJ AND TRAILERS

Since 1974

Leasing & Financing Available

Water Tank Trailers





Standard Specifications

- * Trailer built to suit customer application and budget.
 - * 3 to 30 Ton Trailers.
 - * Single, Tandem or Tri Axle Trailers.
 - * Deck over or between wheels style.
 - * 300 to 3000 USG low profile oval or round poly tank with UV Inhibitors or stainless steel
 - * Deck size to fit tank, pump, hose reel, motor, power connections and tool boxes.
 - * Steel checker plate deck or expanded metal.
 - * Electric, Hydraulic or Air Breaks.
 - * Tires & Rims to fit load capacity.
 - * Heavy Duty Suspension to fit load Capacity.
 - * Tank securely fitted to the trailer bed, preventing shift movement, straps, bands and/or saddles prevent chafing of the poly tank.
 - * Tank with bottom/end sump, plug and seal for total drainage capability.
 - * Fill well 16" plus 2" NPT hole with cover plugs and seal.
 - * 4 HP min, Honda model GX120 or 5.5 HP Honda model GX160 air cooled engine with oil alert.
 - * 2" Honda WP 20X or equal centrifugal pump c/w aluminum housing & frost removal plug.
 - * Motor & pump integrally mounted within a removable caged frame assembly.
 - * Water pump delivery approx 500 LPM @ 4000 RPM and capable of 26m head.
 - * Hannay, Nordic, or Summit brand, power driven or manual hose reel.
 - * Reel to be fitted with up to 150' of 1" or 1 1/4" hose c/w end fittings and heavy duty adjustable spray nozzle.
 - * 2" return hose from tank to pump.
 - * Reel with manual rewind provision with crank handle provided.
 - * Reel to be capable of working at operating pressures without distortion to the side flanges.
 - * Reel piping and swivel union to be 1" minimum.
 - * 2" stainless/brass ball valve to be fitted at tank bottom/end for shut off purposes.
 - * 12 VDC HD battery in lockable box.
 - * Weatherproof rubber sealed on/off switch for the battery assembly.
 - * Front landing jack to fit load capacity.
 - * Sealed type marker and tail lights wired to DOT Specifications to one terminal block at front. No outside exposed connections.
- All connections are heat shrink sealed and loomed in corrugated tubing.
- * Primed with Allcure Grey HS Primer, painted your colour choice from our colour chart and frame seams undercoated.
 - * We provide Limited 3 Year Pro-Rated Major Structural Warranty (Canada ONLY) and 1 year on parts.



Options

- * Tank to be fitted with the appropriate number of baffle balls.
- * Front A frame Tool Box.
- * LED lights.
- * Spare tire, wheel and storage bracket.



Sales: (416) 298-4482
Parts & Service (416) 298-6355
Fax: (416) 298-4480
Toll Free: (877) 294-4482
email: info@jjtrailer.com
www.jjtrailer.com

Steeles			
Finch	McCoun	Markham	
Sheppard			

345 Finchdene Sq.
Scarborough,
Ontario M1X 1B9